

葛尾村仮設焼却施設 平成30年2月 空間線量率測定結果

測定日	測定項目											
	空間線量率(μ Sv/h)											
	業務用地入口				業務用地北側				業務用地境界			
	モニタリングポスト				モニタリングポスト				NAIシンチレーション式サーベイメータ			
	朝	昼	夕	夜	朝	昼	夕	夜	東	南	西	北
1	0.806	0.818	0.812	0.811	0.935	0.946	0.948	0.940	—	—	—	—
2	0.811	0.813	0.811	0.806	0.945	0.945	0.947	0.942	—	—	—	—
3	0.808	0.825	0.820	0.819	0.949	0.962	0.964	0.969	—	—	—	—
4	0.816	0.830	0.826	0.826	0.961	0.979	0.988	0.985	—	—	—	—
5	0.819	0.834	0.827	0.827	0.981	0.993	0.999	0.989	—	—	—	—
6	0.813	0.833	0.826	0.822	0.985	0.993	1.001	0.994	0.84	1.12	0.42	0.80
7	0.820	0.836	0.828	0.821	0.997	1.005	1.010	1.000	—	—	—	—
8	0.821	0.837	0.828	0.825	0.999	1.009	1.012	1.004	—	—	—	—
9	0.819	0.838	0.828	0.827	1.004	1.015	1.016	1.020	—	—	—	—
10	0.831	0.845	0.838	0.847	1.019	1.031	1.037	1.046	—	—	—	—
11	0.846	0.862	0.857	0.853	1.042	1.060	1.070	1.059	—	—	—	—
12	0.850	0.852	0.839	0.836	1.057	1.051	1.045	1.041	—	—	—	—
13	0.827	0.835	0.833	0.829	1.034	1.041	1.034	1.039	1.02	1.39	0.48	0.94
14	0.831	0.847	0.841	0.845	1.034	1.051	1.057	1.061	—	—	—	—
15	0.842	0.847	0.843	0.839	1.059	1.063	1.064	1.055	—	—	—	—
16	0.837	0.853	0.846	0.849	1.054	1.064	1.068	1.069	—	—	—	—
17	0.844	0.852	0.837	0.814	1.070	1.073	1.054	1.026	—	—	—	—
18	0.795	0.805	0.796	0.795	1.008	1.013	1.016	1.012	—	—	—	—
19	0.794	0.814	0.807	0.808	1.015	1.030	1.037	1.037	—	—	—	—
20	0.811	0.823	0.815	0.811	1.040	1.049	1.046	1.041	0.95	1.35	0.45	0.91
21	0.798	0.807	0.804	0.800	1.030	1.040	1.035	1.030	—	—	—	—
22	0.795	0.806	0.805	0.807	1.034	1.039	1.042	1.039	—	—	—	—
23	0.806	0.815	0.808	0.811	1.037	1.051	1.049	1.052	—	—	—	—
24	0.805	0.822	0.809	0.805	1.045	1.060	1.047	1.041	—	—	—	—
25	0.800	0.818	0.812	0.814	1.040	1.056	1.054	1.054	—	—	—	—
26	0.804	0.821	0.810	0.806	1.042	1.057	1.058	1.054	—	—	—	—
27	0.805	0.823	0.807	0.807	1.050	1.065	1.052	1.048	1.01	1.28	0.51	0.89
28	0.810	0.815	0.810	0.816	1.051	1.060	1.060	1.061	—	—	—	—

備考